

Technical Specifications - 300 IX

- Overall dimensions (A x B x C) 609x509x481
- Installation area (D x E) 501x409
- Blade diameter 300 mm
- Blade speed 250 rpm
- Slice thickness 0 to 16 mm
- Carriage travel 297 mm
- Electrical protection IPX3
- Net weight 26,5 Kg
- Electrical specifications 220-230 V - 50 hz / 242W a.c. monophase 120 V - 60 hz / 242W a.c. monophase, 220-230V, 380-400V / 350W a.c. threephase
- Cutting capacity Ø 220 mm - 255 x 220 mm

Standard features

- Belt transmission
- Easy to use built-in sharpener
- Great slicing accuracy
- Low loading height to reduce the operator strain
- Carriage with swinging sharpener pusher
- Reduced foot counter space
- Removable sharpener, blade cover and slice deflector for easy cleaning
- In compliance with European Norms : 2006/42/CE (machinery standards); 1935/2004/CE (food material standards); 2006/95/CE (low voltage standards); 2002/95/CE (RoHS standards); and European standards EN 1974:1998 (slicer – hygiene and safety requirements); EN 60204-1 (safety of machinery); EN 55014 (electromagnetic compatibility)
- Perfect slip grooves for a more performing sliding movement
- Tilting away carriage